



WHY CHOOSE FILL-RITE?

Accurate to 1%, this turbine meter sets the standard for accuracy, ease of use and safety. It has factory presets for 20 fluids and UL/ATEX listing on the entire meter, not just the electronics as competing brands have. Replaceable AA batteries keep your meter running and downtime to a minimum. A rubber boot helps protect the meter and electronics from impact damage. For a robust meter you can depend on, choose Fill-Rite, the most trusted name in pumps and meters.

- Install it where you need it, even at the end of the hose
- Measure gallons, liters, quarts, pints, and ounces with one meter
- A priority on safety with intrinsically safe electronics and near global regulatory approvals provide peace-of-mind



TurbineBrochure-12.16v.3



FILL-RITE
A GORMAN-RUPP COMPANY



IN-LINE DIGITAL TURBINE METER

+/- 1% ACCURACY

FACTORY & FIELD CALIBRATIONS

GLOBAL CERTIFICATIONS

FILL-RITE
A GORMAN-RUPP COMPANY



IN-LINE DIGITAL TURBINE METER

+/- 1% ACCURACY

FACTORY & FIELD CALIBRATIONS

GLOBAL CERTIFICATIONS



ALUMINUM

COMMON COMPATIBLE FUELS:
Gasoline, Diesel, Jet Fuel, Heptane,
Kerosene, Mineral Spirits

**UL ATEX LISTED
ELECTRONICS AND
MECHANICAL
COMPONENTS
FOR ADDED SAFETY**



*Includes 1" to 3/4" reducer bushings

	TT10AN*	TT10AB
FLOW RATE (GPM/LPM)	2-35 / 8-132	2-35 / 8-132
OPERATING PRESSURE	50 psi	50 psi
INLET/OUTLET	1" NPT	1" BSPP
METER ACCURACY	+/- 1.00%	+/- 1.00%
UNITS OF MEASURE	Ounces, pints, quarts, liters, or gallons	
WETTED MATERIALS	Aluminum, Acetal, SS, Gold	
OPERATING TEMP (°F/°C)	-40°F-176°F / -40°C-60°C	
POWER SOURCE	2 AA Batteries	2 AA Batteries
CERTIFICATIONS	UL/cUL, CE, ATEX, IECEx	

NICKEL PLATED

COMMON COMPATIBLE FUELS:
E85, B100 Bio-Diesel, Gasoline,
Diesel, Non-Potable Water, Jet Fuel,
Lavatory Water, Mineral Spirits



	TT10ANC	TT10ABC
FLOW RATE (GPM/LPM)	2-35 / 8-132	2-35 / 8-132
OPERATING PRESSURE	50 psi	50 psi
INLET/OUTLET	1" NPT	1" BSPP
METER ACCURACY	+/- 1.00%	+/- 1.00%
UNITS OF MEASURE	Ounces, pints, quarts, liters, or gallons	
WETTED MATERIALS	Nickel-Plated Aluminum, Acetal, SS, Gold	
OPERATING TEMP (°F/°C)	-40°F-176°F / -40°C-60°C	
POWER SOURCE	2 AA Batteries	2 AA Batteries
CERTIFICATIONS	UL/cUL, CE, ATEX, IECEx	

POLYMER

COMMON COMPATIBLE FUELS:
DEF/Ad Blue, Anti-Freeze,
De-icing Fluid, Non-Potable Water,
and Other Chemicals



**INSTALL IT WHERE YOU NEED IT
EVEN AT THE END OF THE HOSE**

	TT10PN	TT10PB
FLOW RATE (GPM/LPM)	2-35 / 8-132	2-35 / 8-132
OPERATING PRESSURE	50 psi	50 psi
INLET/OUTLET	1" NPT	1" BSPP
METER ACCURACY	+/- 1.00%	+/- 1.00%
UNITS OF MEASURE	Ounces, pints, quarts, liters, or gallons	
WETTED MATERIALS	PP, UHMWPE, SS, Gold	
OPERATING TEMP (°F/°C)	-15°F-176°F / -26°C-60°C	
POWER SOURCE	2 AA Batteries	2 AA Batteries
CERTIFICATIONS	UL/cUL, CE, ATEX, IECEx	