

NX25-DDCNB

WITH



FILL-RITE®

ON →
OFF ←



THE INDUSTRY'S FIRST

CONTINUOUS DUTY FUEL TRANSFER PUMP

nextec Intelligence® is an exclusive array of design advancements, technologies and user functionalities that take pump performance to unprecedented levels. Intelligent Tones™ inform when attention is needed. A variable speed motor automatically adjusts for peak performance with improved suction lift. More compact, lighter, and less amp draw—it sets a new standard for efficiency.

THE FUTURE OF FUEL TRANSFER IS HERE

GR
GORMAN-RUPP
COMPANY



nextec Intelligence® - Predicts, Protects, Performs

	NX25-DDC SERIES			
FLOW RATE	25 GPM / 95 LPM**			
VOLTAGE	12 TO 24V DC			
INLET/OUTLET	1 - ¼" NPT / 1" NPT	1" NPT / 1" NPT	1 - ¼" BSP / 1" BSP	1" BSP / 1" BSP
MTLS OF CONST	CAST IRON PUMP HOUSING			
MOUNTING	2" NPT BUNG	FOOT MOUNT	2" BSP BUNG	FOOT MOUNT
AMP (FLA)	29 AMPS			
HORSEPOWER	1/3 HP			
COMPATIBLE FLUIDS	DIESEL, GASOLINE, BIO-DIESEL UP TO B20, E15, KEROSENE, MINERAL SPIRITS, METHANOL (UP TO 15%)			
DUTY CYCLE	CONTINUOUS DUTY FOR FUEL TRANSFER			
WARRANTY	LIMITED LIFETIME WARRANTY†			
CERTIFICATIONS	UL/CUL, CE, ATEX, IECEX			



Bung Mount Configuration
NX25-DDCNB-AA



Foot Mount Configuration
NX25-DDCNF-AA

Features & Benefits

- Continuous Duty***
Nonstop performance eliminates downtime, saving you time and money
- Remote On/Off**
Remote switching capability for tall, above ground tanks
- Intelligent Tones**
Simplify troubleshooting with audible tones that indicate when and where attention is needed
- Variable Speed Motor**
Pump actively adjusts its speed for optimal performance and improves suction lift
- Lighter**
Great for mobile tanks, even aluminum
- Auto Power Down**
After 20 minutes of inactivity the pump will turn itself off, reducing energy costs
- Magnetic Switch**
Smooth operation and completely field replaceable
- Reduced Vapor Lock**
Keep your operation running in the harshest summer temperatures
- Slow Down in Bypass**
Reduce energy consumption and preserve the life of wetted components

*Rated continuous duty for fuel transfer **Adding accessories will affect flow rate †Warranty details can be found at fillrite.com

FIL-BR-G23v.1



CUSTOMER SUPPORT: (800) 634-2695
 TECHNICAL SUPPORT: (260) 747-7524

FILLRITE.COM

